WILLS WING 500 West Blueridge Orange CA USA 92865-4206
Fax (714) 998-0647 Phone (714) 998-6359
Web Site: http://www.willswing.com

Installing the Wills Wing Raked Tips

The raked tips are specific to the glider size – T2C 136, T2C 144, T2C 154 – you must have the correct tips.

Your sail must be configured to be compatible with the raked tips. In general, this means a serial number greater than 40841, and a production date after February 9th, 2014

There are (2) 12 inch carbon rods stowed in the edge-seam of each raked tip. The larger one is about 0.10 inches diameter and the smaller about 0.06 inches. The smaller one always remains completely in the tip but the larger one is only stowed in the seam for protection during transport.

Open the Velcro completely between the top and bottom surface at the tip.

Pull 4 inches of the 0.10 inch diameter rod out from the seam before you install the tips. This extension should be "plugged in" to the sail between the wand lever and the adjacent seam at the edge of the sail in order to support the raked tip and align it properly with the sail body before securing the Velcro.

Carefully align the mating Velcro surfaces of the raked tip to those of the sail.

Attach the Velcro on the sail top surface to the top surface of the raked tip. Then separate any Velcro that has become attached on the bottom, pull any slack out of the bottom surface, and make a smooth attachment of the bottom surface of the sail to the bottom surface of the Velcro.



